

## TIPO DE CONTENEDORES

### External measurements:

Length: 6,058 mm  
Width: 2,438 mm  
Height: 2,591 mm

### Internal measurements:

Length: 5,910 mm  
Width: 2,340 mm  
Height: 2,388 mm

### Entrances:

Width: 2,346 mm  
Height: 2,282 mm  
Cubic Capacity: 33.2 m3

### Weights:

Maximun weight: 24,000 Kg  
Tare weight: 2,080 Kg  
Cargo: 21,920 Kg

### Characteristics:

Corner casting for handling with cargo.

### Standard Container for non-perishable cargo(20')



### External measurements:

Length: 12,192mm  
Width: 2,438 mm  
Height: 2,591 mm

### Internal measurements:

Length: 12,044 mm  
Width: 2,342 mm  
Height: 2,380 mm

### Entrances:

Width: 2,337 mm  
Height: 2,280 mm  
Cubic Capacity: 67.6 m3

### Weights:

Maximun weight: 30,480 Kg  
Tare weight: 3,550 Kg  
Cargo: 26,930 Kg

### Characteristics:

Corner casting for handling with cargo.

### Standard Container for non-perishable cargo(40')



### External measurements:

Length: 12,192mm  
Width: 2,438 mm  
Height: 2,895 mm

### Internal measurements:

Length: 12,032 mm  
Width: 2,350 mm  
Height: 2,695 mm

### Entrances:

Width: 2,338 mm  
Height: 2,585 mm  
Cubic Capacity: 76.2 m3

### High Cube Container (40')



**Weights:**

Maximun weight: 30,480 Kg

Tare weight: 4,150 Kg

Cargo: 26,330 Kg

**Characteristics:**

Corner casting for handling with cargo.

**External measurements:**

Length: 6,058 mm

Width: 2,438 mm

Height: 2,438 mm

**Internal measurements:**

Length: 5,717 mm

Width: 2,267 mm

Height: 2,117 mm

**Entrances:**

Width: 2,267 mm

Height: 2,115 mm

Cubic Capacity: 27.4 m<sup>3</sup>

**Weights:**

Maximun weight: 24,000 Kg

Tare weight: 2,800 Kg

**Characteristics:**

Aluminum floor. Reinforced steel doors.

Stainless steel casing. Clip-on recess.

## Insulated Container



**External measurements:**

Length: 6,058 mm

Width: 2,438 mm

Height: 2,591 mm

**Internal measurements:**

Length: 5,498 mm

Width: 2,270 mm

Height: 2,267 mm

**Entrance:**

Width: 2,270 mm

Height: 2,210 mm

Cubic Capacity: 28.3 m<sup>3</sup>

**Weights:**

Maximun weight: 25,400 Kg

Tare weight: 3,040 Kg

Cargo: 22,360 Kg

**Characteristics:**

Aluminum floor. Reinforced teel door.

Stainless steel casing Power generator recess.

## Refrigerated Container



**External measurements:**

Length: 6,068 mm

Width: 2,438 mm

Height: 2,591 mm

**Internal measurements:**

Length: 5,900 mm

## Ventilated Container

Width: 2,323 mm  
Height: 2,367 mm

Ventilation:  
Top: 9,000 cm<sup>3</sup> x side  
Base: 1,000 cm<sup>3</sup> x side  
Cubic Capacity: 32.6 m<sup>3</sup>

Weights:  
Maximum weight: 24,000 Kg  
Tare weight: 2,650 Kg  
Cargo: 21,350 Kg

Characteristics:  
Sling for handling with cargo. 20,000 cm<sup>3</sup>  
permanent ventilation.



External measurements:  
Length: 6,058 mm / 12, 192 mm  
Width: 2,438 mm / 2,438 mm  
Height: 2,591 mm / 2,591 mm

Internal measurements:  
Access from top  
Length: 5,792 / 11,883 mm  
Width: 2,225 mm / 2,152mm

Entrances:  
Length: 2,336 mm / 2,337 mm  
Height: 2,233 mm / 2,280 mm

Weights:  
Maximum: 24,000 / 30,820 kg  
Tare weight: 2,050 / 3,800 kg  
Cargo: 21,950 / 27,020 kg  
Central height of arches:  
2,370 mm / 2,380 mm  
Side height of arches:  
2,320 mm / 2,330 mm  
Length of side panel:  
2,346 mm / 2,342 mm  
Cubic Capacity: 32.2 m<sup>3</sup> / 65.6 m<sup>3</sup>

Characteristics:  
Sling for handling with cargo (20') Hoisting  
up.

External measurements:  
Length: 6,058 mm / 12, 192 mm  
Width: 2,438 mm / 2,438 mm  
Height: 226 mm / 628 mm

Internal measurements:  
Length of platform:  
6,020 mm / 12,150 mm  
Width of platform:  
2,413 mm / 2,290 mm  
Cubic Capacity: 29 m<sup>3</sup> / 67 m<sup>3</sup>

Characteristics:  
Sling for handling with cargo Steel platform.  
Hoisting up.

### Open Top Container (20'/40')



### Platform Container (20'/40')



External measurements:

Length: 6,058 mm / 12, 192 mm  
Width: 2,438 mm / 2,438 mm  
Height: 2,591 mm / 2,591 mm  
Folded height: 555 mm / 700 mm  
Platform height: 271mm / 605 mm

Internal measurements:

Cargo access / top: 5,908mm / 12,020 mm  
Cargo access / side: 5,508 mm / 11,730 mm  
Width: 2,387mm / 2,230 mm Width between struts: 2,182mm / 2,230 mm  
Width between shafts: 2,190 mm / 2,100 mm  
Height: 2,320 mm / 1,986 mm  
Cubic Capacity: 28.9 m3 / 67 m3

Weights:

Maximum: 25,400 kg / 45,000 kg  
Tare weight: 2,845 kg / 5,180 kg  
Cargo: 22,555 kg / 39,820 kg

Characteristics:

Fold-up spring-loaded panels Sling for handling with cargo.

### Flack Rack (20'/40')



External measurements:

Length: 6,058 mm  
Width: 2,438 mm  
Height: 2,591 mm

### Tank Container



External measurements:

Length: 6,058 mm  
Width: 2,438 mm  
Height: 2,591 mm

Internal measurements:

Length: 5,838 mm  
Width: 2,366 mm  
Height: 2,374 mm

Front opening:

Width: 2,144 mm  
Height: 500 mm

Rear opening:

Width: 280 mm  
Height: 300 mm  
Cubic capacity: 32.7 m3

Top openings:

500 mm diameter  
Maximum cargo weight: 28,030 kg  
Weight per container: 2,540 kg

### Bulk Container



Characteristics:  
Sling of shifting with cargo and three access  
openings on top.